

PELLERANO

ATTREZZATURE SPECIALI PER L'AGRICOLTURA

STRETCHING NYLON-MULCHER mod.NS



The Stretching Nylon-Mulchers mod.NS extend both the transparent film on the tunnels and the film of mulching.

They are all adjustable and frictioned because they are robust and at the same time delicate with the plastic allowing to work with very thin films (0.020 mm thick).

The Stretching Nylon-mulching machines mod.NS have a very high level of adjustability that not only allows each organ to be moved in all directions (above, below, right, left, forward, back) but also to be able to carry out this operation in at least 2 or 3 different modes. In this way you can from time to time decide the most convenient and quickest adjustment mode at that time. This gives the Stretching Nylon-mulching machines mod.NS an extreme simplicity and immediacy of use.

The Stretching Nylon-mulching machine mod. NS works using adjustable disks. This machine still uses the plastic film with the earth thanks to 2 adjustable disks.

It has other 2 front furrow discs that allow you to have no problem from soil compaction carried out by the tractor in the previous passages on the same ground when the mulch was put.

This machine was created to minimize soil compaction by allowing it to be used on all worked terrains.

Another feature of the Stretching Nylon-mulching model NS is the extreme delicacy with which the plastic film or non-woven fabric (TNT) works thanks to 2 pairs of adjustable wheels. This allows you to work even the thinnest films (mm.0.020 thick) easily.

From the function of the curvature of the plastic film or TNT given by the so-called "false adjustable arc" derives the correct tension and the duration of the film itself.

Since the arches don't all have the same shape, the inclination of the "false bow" is adjustable, obtaining the ideal curvature shape for the arch used.

The Stenditunnel-mulching machine mod.NS can carry out many other processes simultaneously with a wide range of optionals.

When used as a mulcher, it can put a hose or an irrigation pipe, bore the mulch before transplanting and distribute fertilizer and plant protection products. All in one step.

PELLERANO

ATTREZZATURE SPECIALI PER L'AGRICOLTURA



Optionals

- clutched Stretching Nylon
- clutched Stretching Tube
- "Tracciafila" dx / sx
- Pre-transplant film bender
- Microgranular electric localized for insecticide and / or crystalline fertilizers
- Localized electric fertilizer spreader
- Bauling kit (2 disks + 2 shares complete with adjustable attachments)
- Adjustable front depth adjustment wheels kit
- Scrapers for discs
- Vomers interchangeable with the front discs
- Rear wheels support with extension

The type of frame of the Stretching Nylon-mulching mod.NS allows to work with very minimal distances between tunnel and tunnel.

The possibility of adjusting the frame height allows you to carry it "out of the way" of the tunnels already placed reaching the minimum distance.

For special cases we have added the interchangeable front coulters as optionals to break the ground so that the rear discs find a more loose soil.

Also for the rear support wheels we have added among the optionals the expansions of the frame that lengthen it, allowing the wheels to be positioned a lot behind almost the same space as the reinforcement discs.

TECHNICAL FEATURES

Stretching Nylon-mulching machine mod.NS230 - weight. Kg. 390 - film max cm.160 - tractors: from 50 upwards

Stretching Nylon-mulching machine mod.NS260 - weight. Kg. 430 - film max cm.200 - tractors: from 50 upwards